


6P6C RJ-11 Coupler Module, Pin 1-1

PRODUCT SPECIFICATION

Package includes:

A. Pin 1-1 6P6C RJ-11 Coupler Module, 1 pc



Features and Benefits:

- Provides pin 1-1 RJ-11 voice coupling
- Reduced rear footprint allows for greater connectivity density and provides for more port configurations in a smaller area
- Compatible with all IC107 faceplates, inserts, surface mount boxes, and blank patch panels
- Compatible with all IC108 furniture faceplates, bezels, and surface mount boxes
- Available in black, gray, ivory, and white
- ANSI/TIA-568-C and UL 1863 compliant



MODULE, COUPLER, RJ-11, PIN 1-1

ITEM NO. IC107C6RXX
DWG NO. PS107C6R00



REV. B
PAGE NO. 1




CUSTOMER CARE / TECHNICAL SUPPORT * CSR@ICC.COM / 888-ASK-4-ICC (275-4422) * 2100 E. Valencia Dr, Suite D, Fullerton, CA 92831 * www.icc.com



FRONT



REAR



NOTE: UNLESS OTHERWISE SPECIFIED

1. ELECTRICAL:

- A. CURRENT RATING: 1.5 AMPS MAX
- B. VOLTAGE RATING: 150 VOLTS AC
- C. DIELECTRIC WITHSTANDING VOLTAGE: 1000 VOLTS RMS, 60 HZ
- D. INSULATION RESISTANCE: > 10 MOHMS

2. MECHANICAL:

- A. MATING FORCE: 5 LBS MAX
- B. UNMATING FORCE: 5 LBS MAX
- C. PLUG RETENTION IN JACK: 20 LBS MIN
- D. DURABILITY: 750 CYCLES

3. MATERIAL & FINISH:

- A. HOUSING: ABS, UL 94V-0
- B. COLOR: BK-BLACK, GY-GRAY, IV-IVORY, & WH-WHITE
- C. CONTACT: PHOSPHOR BRONZE GOLD PLATING OVER 100 MICRO INCH NICKEL
- D. GOLD PLATING: 1.27 MICRON/50 MICRO INCH MIN

WIRING DIAGRAM	
PIN	PIN
1	1
2	2
3	3
4	4
5	5
6	6

UL US FILE NO. 125268

MODULE, COUPLER, RJ-11, PIN 1-1			
ITEM NO.	IC107C6RXX		REV. B
DWG NO.	PS107C6R00		PAGE NO. 2

CUSTOMER CARE / TECHNICAL SUPPORT * CSR@ICC.COM / 888-ASK-4-ICC (275-4422) * 2100 E. Valencia Dr, Suite D, Fullerton, CA 92831 * www.icc.com